



技术参数表
specifications

桩锤型号 Model	DD18	DD25	DD35	DD45	DD55	DD65	DD75	DD85	DD105	DD128	DD160	DD180	DD200	DD220
气缸体重量(KG) Cylinder Weight	1800	2500	3500	4500	5500	6500	7500	8500	10500	12800	16000	18000	20000	22000
缸体最大冲程(M) Max.cylinder stroke	2.1	2.5	2.8	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
频率(T/MIN) Frequency	45~60	42~55	40~52	35~50	35~50	35~50	35~50	35~50	35~50	35~50	35~50	35~50	35~50	35~50
最大能量理论值(KJ) Max.impacting energy (Theroretical value)	37.8	57.5	89.6	120	159	189	219	249	309	378	450	540	600	660
耗油量(L/H) Fuel consumption	6.9	10	12	14.5	16	18	21	25	30	38	43	48	50	56
气缸孔径(MM) Cylinder Diamete	φ300	φ370	φ410	φ450	φ500	φ550	φ580	φ600	φ665	φ720	φ780	φ820	φ840	φ900
压缩比 Compressing ratio	18	22	22	22	22	22	25	25	25	28	28	30	30	30
总质量(KG) Total weight	3120	4200	5350	7300	9800	12500	14500	15500	18500	22500	33000	34800	38500	42500
导轨形式 Guideway	槽钢 channel steel	槽钢/圆管 channel steel /round pipe 圆管73mm或者102mm round pipe 73mm or 102mm												
导轨中心距(MM) Guidewaycenter distance	360	360/ 330	360/ 330	360/ 330	360/ 330	330/ 600	330/ 600	600	600	600	600	600	600	600
备注 Remark	可专配圆管导管 Maybe equipped with round pipe													